

Main

Range	Linergy
Product name	HK
Product or Component Type	Plug outlet
Poles description	3P
[I _{th}] conventional free air thermal current	16 A
I ² t on activation	100000 A ² .s
Number of points	2
Number of cables	3 0.004 in ² (2.5 mm ²)
Cable length	0.7 ft (0.2 m)
Quantity per Set	Set of 6

Complementary

[Ui] rated insulation voltage	600 V CSA 600 V UL 690 V IEC 60439-1
Peak current	25 kA
Width	1.4 in (36 mm)
Height	1.8 in (46 mm)
Depth	1.5 in (38 mm)
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Standards	IEC 60439
Product Certifications	DNV[RETURN]LROS (Lloyds register of shipping)[RETURN]UL[RETURN]CSA

Ordering and shipping details

Category	US10I1122623
Discount Schedule	0I11
GTIN	3389110576818
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.378 in (3.500 cm)
Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	4.724 in (12.000 cm)
Package 1 Weight	1.552 oz (44.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	5.000000000 in (12.700 cm)
Package 2 Width	5.118 in (13.000 cm)
Package 2 Length	5.906 in (15.000 cm)
Package 2 Weight	11.464 oz (325.000 g)

Unit Type of Package 3	S04
Number of Units in Package 3	96
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	15.748 in (40.000 cm)
Package 3 Length	23.622 in (60.000 cm)
Package 3 Weight	13.089 lb(US) (5.937 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------