

Product data sheet

Specifications



Empty enclosures for standard starters, TeSys LE, with 2 pushbuttons, for LE1D09 and LE1D12

DE1DS1

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	TeSys
Range	TeSys
Device short name	DE1D
Product or Component Type	Enclosure
Material	Polycarbonate
Device composition	Contacteur ordered separately Thermal overload relay ordered separately
Product Compatibility	LE1D09 LE1D12
Control type	Push-button start Green I Push-button stop/reset Red O

Complementary

Cable entry number	2 ISO20 top 2 ISO20 bottom 2 Pg 13 bottom 2 Pg 16 bottom
Height	6.5 in (166 mm)
Width	3.5 in (88 mm)
Depth	5.9 in (150 mm)
Product Weight	0.7 lb(US) (0.3 kg)

Environment

IP degree of protection	IP65 IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	23...104 °F (-5...40 °C)
Environmental characteristic	Standard environment
Product Certifications	UKCA

Ordering and shipping details

Category	US1CP1018401
Discount Schedule	CP10
GTIN	3389110087048
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	FR
-------------------	----

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.890 in (17.500 cm)
Package 1 Width	6.496 in (16.500 cm)
Package 1 Length	8.465 in (21.500 cm)
Package weight(Lbs)	18.977 oz (538.000 g)
Unit Type of Package 2	P06
Number of Units in Package 2	30
Package 2 Height	29.528 in (75.000 cm)
Package 2 Width	23.622 in (60.000 cm)
Package 2 Length	31.496 in (80.000 cm)
Package 2 Weight	63.052 lb(US) (28.600 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	429 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	424 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	9f35ee05-3751-48fa-a30a-96c8b2cda02b
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	37
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.