

Product data sheet

Specifications



gearbox straight teeth GBX, Lexium,
80mm, reduction 5:1 , 7arc.min,
110N.m

GBX080005K

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range Compatibility	Lexium SD3 Lexium 32 Lexium 28 Lexium 62 Lexium 62 ILM Lexium ILS Lexium 32i Lexium 52
Gear box type	Straight teeth
Product or Component Type	Planetary gearbox
Device short name	GBX
Product compatibility	BMI 2.8 in (70 mm), 2 BMI 2.8 in (70 mm), 3 BMH 3.9 in (100 mm), 1 BMH 3.9 in (100 mm), 2 BMH 3.9 in (100 mm), 3 BSH 3.9 in (100 mm), 1 BSH 3.9 in (100 mm), 2 BSH 3.9 in (100 mm), 3 BRS3 ILS 3.3 in (85 mm), 1 ILS 3.3 in (85 mm), 2 ILS 3.3 in (85 mm), 3 BCH2 3.1 in (80 mm), 1 BCH2 3.1 in (80 mm), 2 SH3 MH3 ILM
Gearbox external diameter	3.1 in (80 mm)
Reduction ratio	5:1

Complementary

Maximum torsional backlash	7 arc.min
Torsional rigidity	6 N.m/arcmin
Housing Colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Mounting position	Any position
Efficiency	97.0 %
Maximum radial force Fr	650 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum axial force Fa	1200 N 100 rpm, during 30000 hour at 30°C
moment of inertia	0.455 kg.cm²
Continuous output torque	973.6 lbf.in (110 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	1557.7 lbf.in (176 N.m) 100 rpm 86 °F (30 °C)
Product Weight	4.6 lb(US) (2.1 kg)
Input diameter	0.7 in (19.0 mm)
No load running torque	0.9 lbf.in (0.1 N.m)
Reduction ratio	5
Compatibility code	GBX
Internal length	2.8 in (72.0 mm)

Environment

Noise level	60 dB 1 m, no-load
IP Degree of Protection	Shaft output IP54
ambient temperature for operation	-13...194 °F (-25...90 °C)

Ordering and shipping details

Category	US1PC5318283
Discount Schedule	PC53
GTIN	3606480388330
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.378 in (16.200 cm)
Package 1 Width	4.252 in (10.800 cm)
Package 1 Length	4.331 in (11.000 cm)
Package weight(Lbs)	4.325 lb(US) (1.962 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	5
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	22.412 lb(US) (10.166 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	7c9e597c-8ccc-4daf-95fb-5d67fc70d561
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer


Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Dimensions Drawings

Dimensions with Servo Motor Adaptation Kit



- (1) GBK adaptation kit
- (2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination
- Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
72	40	36	4	22.5	6	80	60 h7	20 h7	M6 x 10	70

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
2.83	1.57	1.42	0.16	0.89	0.24	3.15	2.36 h7	0.79 h7	M6 x 0.39	2.76