

Product data sheet

Specifications



Motor circuit breaker, TeSys Deca, 2 normally open and 2 normally closed contacts, SDx contact module, GV4PEM

GV4ADM1111

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Device short name	GV4A
Product or Component Type	Auxiliary contact block
Product Compatibility	GV4
Mounting Location	Right side
Auxiliary contacts operation	Signalling
Pole contact composition	2 NO + 2 NC

Complementary

[Ui] rated insulation voltage	250 V IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Protection type	GG fuse 5 A
Rated operational power in VA	400 VA 230...240 V AC-12
Rated operational power in W	50 W 24 V DC-12

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Ordering and shipping details

Category	US10I1122366
Discount Schedule	0I11
GTIN	3606481166753
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package 1 Height	1.2 in (3 cm)
Package 1 Width	3.5 in (9 cm)
Package 1 Length	6.1 in (15.6 cm)
Package weight(Lbs)	5.3 oz (150 g)
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	5.9 in (15 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	6.6 lb(US) (3 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	50a98d63-e355-4cae-a24f-48edbc8c4dc5
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.