Product data sheet

Specifications



Mounting base, for TeSys Giga electronic overload relay LR9G500, independent mounting below contactor LC1G265-500

LA9G3651

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Device short name	LA9G
Product or Component Type	Mounting base
Accessory / separate part category	Installation accessories
Range compatibility	TeSys G LC1G contactor
Product Compatibility	LC1G265...330 LC1G300...475 LR9G500
Quantity per Set	Set of 1

Complementary

[Ie] rated operational current	330 A
IP degree of protection	IP20 conforming to IEC 60529
Height	0.4 in (10 mm)
Width	3.7 in (95 mm)
Depth	5.7 in (145 mm)
thickness	0.2 in (6 mm)
Product Weight	0.9 lb(US) (0.4 kg)

Environment

Operating altitude	9842.52 ft (3000 m) without derating 5000 m with derating factor
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Pollution degree	3 IEC 60947-1
Ambient air temperature for operation	-40…140 °F (-40…60 °C)
Ambient Air Temperature for Storage	-76…176 °F (-60…80 °C)

Ordering and shipping details

Category	US10I1222328
Discount Schedule	0I12
GTIN	3606481916563

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.8 in (2.0 cm)
Package 1 Width	7.09 in (18.0 cm)
Package 1 Length	7.9 in (20.0 cm)
Package weight(Lbs)	8.4 oz (239.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	8.865 lb(US) (4.021 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	958748fb-37b2-4e37-985e-0763521c22ab
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.