Product data sheet

Specifications

Busbar support, Linergy BZ, Support 3P for 60 Interaxis Busbar IEC

LA9ZX01495

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	Linergy
Product or Component Type	Busbar support
Device short name	LA9Z
Product name	BZ
Quantity per Set	Set of 10

Complementary

Range compatibility	TeSys
[Ui] rated insulation voltage	690 V IEC 60947-1 690 V NF C 20-040
Permissible current	200 A 12 x 5 mm 250 A 15 x 5 mm 320 A 20 x 5 mm 400 A 25 x 5 mm 450 A 30 x 5 mm 360 A 12 x 10 mm 520 A 20 x 10 mm 630 A 30 x 10 mm
Distance between supports	22.4 in (570 mm)
Busbar pitch	2.4 in (60 mm)
Poles description	3P
color	Gray

Environment

IP degree of protection	IP20 with protective cover
Temperature resistance	257 °F (125 °C)
Standards	UL 508 IEC 61439-2
Product Certifications	IEC

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3606480100147
Returnability	No
Country of origin	DE

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.787 in (2.000 cm)
Package 1 Width	2.480 in (6.300 cm)
Package 1 Length	7.638 in (19.400 cm)
Package weight(Lbs)	5.044 oz (143.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.512 in (14.000 cm)
Package 2 Width	4.488 in (11.400 cm)
Package 2 Length	8.189 in (20.800 cm)
Package 2 Weight	3.195 lb(US) (1.449 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	50
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	17.593 lb(US) (7.980 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen content performance	**Halogen free plastic parts product**
PVC free	**Yes**
Silicon free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Take-back	**No**