

# Product data sheet

Specifications



IEC contactor, TeSys Deca, nonreversing, 80A resistive, 4 pole, 4 NO, 100/250VAC/VDC coil, open style

LC1DT80A6KUE

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

|                                |                                                              |
|--------------------------------|--------------------------------------------------------------|
| Range of Product               | TeSys Deca Advanced                                          |
| Product or Component Type      | Contactors                                                   |
| Device short name              | LC1D                                                         |
| Contactors application         | Resistive load                                               |
| Utilisation category           | AC-1                                                         |
| Poles description              | 4P                                                           |
| [Ue] rated operational voltage | Power circuit <= 690 V AC 25...400 Hz                        |
| [Ie] rated operational current | 80 A (at <140 °F (60 °C)) at <= 440 V AC-1 for power circuit |
| [Uc] control circuit voltage   | 100...250 V AC 50/60 Hz<br>100...250 V DC                    |

## Complementary

|                                             |                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility code                          | LC1D                                                                                                                                                                                                                                                                                                                       |
| Pole contact composition                    | 4 NO                                                                                                                                                                                                                                                                                                                       |
| Protective cover                            | With                                                                                                                                                                                                                                                                                                                       |
| [Ith] conventional free air thermal current | 80 A (at 140 °F (60 °C)) for power circuit<br>10 A (at 140 °F (60 °C)) for signalling circuit                                                                                                                                                                                                                              |
| Irms rated making capacity                  | 1000 A at 440 V for power circuit conforming to IEC 60947<br>140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1                                                                                                                                    |
| Rated breaking capacity                     | 1000 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                  |
| [Icw] rated short-time withstand current    | 110 A 104 °F (40 °C) - 10 min for power circuit<br>260 A 104 °F (40 °C) - 1 min for power circuit<br>520 A 104 °F (40 °C) - 10 s for power circuit<br>900 A 104 °F (40 °C) - 1 s for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated fuse rating                      | 125 A gG at <= 690 V coordination type 1 for power circuit<br>125 A gG at <= 690 V coordination type 2 for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947-5-1                                                                                                                                     |
| Average impedance                           | 1.6 mOhm - Ith 80 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                |
| Power dissipation per pole                  | 10.2 W AC-1                                                                                                                                                                                                                                                                                                                |
| [Ui] rated insulation voltage               | Power circuit 690 V IEC 60947-4-1<br>Signalling circuit 690 V IEC 60947-1                                                                                                                                                                                                                                                  |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                                                        |
| Pollution degree                            | 3                                                                                                                                                                                                                                                                                                                          |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Uimp] rated impulse withstand voltage | 6 kV IEC 60947                                                                                                                                                                                                                                                                                                                                                                                              |
| Safety reliability level               | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1                                                                                                                                                                                                                                                                    |
| Mechanical durability                  | 10 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                  |
| Electrical durability                  | 0.5 Mcycles 80 A AC-1 <= 440 V                                                                                                                                                                                                                                                                                                                                                                              |
| Control circuit type                   | AC/DC 50/60 Hz AC/DC electronic                                                                                                                                                                                                                                                                                                                                                                             |
| Coil technology                        | Built-in bidirectional peak limiting                                                                                                                                                                                                                                                                                                                                                                        |
| Control circuit voltage limits         | <= 0.1 Uc (-40...158 °F (-40...70 °C)):drop-out AC/DC<br>0.85...1.1 Uc (-40...140 °F (-40...60 °C)):operational AC/DC<br>1...1.1 Uc (140...158 °F (60...70 °C)):operational AC/DC                                                                                                                                                                                                                           |
| Inrush power in VA                     | 22 VA 50/60 Hz (at 68 °F (20 °C))                                                                                                                                                                                                                                                                                                                                                                           |
| Inrush power in W                      | 20 W 68 °F (20 °C))                                                                                                                                                                                                                                                                                                                                                                                         |
| Hold-in power consumption in VA        | 2.1 VA 50/60 Hz (at 68 °F (20 °C))                                                                                                                                                                                                                                                                                                                                                                          |
| Hold-in power consumption in W         | 1.2 W 68 °F (20 °C)                                                                                                                                                                                                                                                                                                                                                                                         |
| Heat dissipation                       | 1.2 W at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                           |
| Operating time                         | 55...65 ms closing<br>20...80 ms opening                                                                                                                                                                                                                                                                                                                                                                    |
| Maximum operating rate                 | 3600 cyc/h at 60 °C                                                                                                                                                                                                                                                                                                                                                                                         |
| Connections - terminals                | Power circuit: lugs-ring terminals - external diameter: 0.6 in (16.5 mm)<br>Control circuit: lugs-ring terminals - external diameter: 0.3 in (8 mm)                                                                                                                                                                                                                                                         |
| Tightening torque                      | Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5<br>Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5<br>Power circuit 53.1 lbf.in (6 N.m) lugs-ring terminals hexagonal 0.4 in (10 mm) M6<br>Power circuit 53.1 lbf.in (6 N.m) lugs-ring terminals pozidriv No 2 M4<br>Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals pozidriv No 2 M3.5 |
| Auxiliary contact composition          | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                                                                 |
| Auxiliary contacts type                | Mechanically linked 1 NO + 1 NC IEC 60947-5-1<br>Mirror contact 1 NC IEC 60947-4-1                                                                                                                                                                                                                                                                                                                          |
| Signalling circuit frequency           | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                                                                 |
| Minimum switching voltage              | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                 |
| Minimum switching current              | 5 mA for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                 |
| Insulation resistance                  | > 10 MOhm for signalling circuit                                                                                                                                                                                                                                                                                                                                                                            |
| Non-overlap time                       | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                                                                                                                                                                     |
| Mounting Support                       | Plate<br>Rail                                                                                                                                                                                                                                                                                                                                                                                               |

## Environment

|                         |                                                                                               |
|-------------------------|-----------------------------------------------------------------------------------------------|
| Standards               | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>IEC 60335-1 |
| Product Certifications  | CCC<br>CSA<br>EAC<br>UL<br>KC<br>DNV-GL<br>LROS (Lloyds register of shipping)<br>UKCA         |
| IP degree of protection | IP20 front face IEC 60529                                                                     |

|                                                       |                                                                                                                                                                                    |
|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Climatic withstand                                    | IACS E10 exposure to damp heat<br>IEC 60947-1 Annex Q category D exposure to damp heat                                                                                             |
| Permissible ambient air temperature around the device | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating                                                                                                              |
| Operating altitude                                    | 0...9842.52 ft (0...3000 m)                                                                                                                                                        |
| Fire resistance                                       | 1562 °F (850 °C) IEC 60695-2-1                                                                                                                                                     |
| Mechanical robustness                                 | Vibrations contactor open 2 Gn, 5...300 Hz)<br>Vibrations contactor closed 4 Gn, 5...300 Hz)<br>Shocks contactor open 10 Gn for 11 ms)<br>Shocks contactor closed 15 Gn for 11 ms) |
| Height                                                | 4.8 in (122 mm)                                                                                                                                                                    |
| Width                                                 | 2.8 in (70 mm)                                                                                                                                                                     |
| Depth                                                 | 4.7 in (120 mm)                                                                                                                                                                    |
| Product Weight                                        | 2.844 lb(US) (1.290 kg)                                                                                                                                                            |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10I1222357  |
| Discount Schedule | 0I12          |
| GTIN              | 3606489493554 |
| Returnability     | No            |
| Country of origin | FR            |

## Packing Units

|                        |                         |
|------------------------|-------------------------|
| Unit Type of Package 1 | PCE                     |
| Nbr. of units in pkg.  | 1                       |
| Package 1 Height       | 2.8 in (7.0 cm)         |
| Package 1 Width        | 5.4 in (13.8 cm)        |
| Package 1 Length       | 6.02 in (15.3 cm)       |
| Package weight(Lbs)    | 2.560 lb(US) (1.161 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 100 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 8 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 91 kg CO2 eq.                                 |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 2 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | Yes                                                                                    |
| SCIP Number                            | 9bb0b51e-73b5-4128-a86b-723dbbccfe86                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |
| Halogen content performance            | Halogen free plastic parts & cables product                                            |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 64                                                                                                                                                                                                               |
| Circularity Profile           | <a href="#">End of Life Information</a>                                                                                                                                                                          |
| Take-back                     | No                                                                                                                                                                                                               |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Offer Marketing Illustration

Product benefits / Features

### TeSys Deca Contactors



**Reliable**

Multi-standard solutions, high reliability, long mechanical and electrical durability for different sizes, and the most complete accessories.



**Energy efficiency**

These electronic-coil contactors require up to 80 % less energy than electro-mechanical contactors.



**Universal**

Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACH).



Jun 29, 2026

Schneider  
Electric

5

Offer Marketing Illustration

Product benefits / Features



The image shows a TeSys Deca Contactor, a black industrial electrical component. It has a green label with 'TeSys' and 'Schneider Electric' logos. The label also indicates 'Control' and 'LC1 D09'. The device has multiple terminals on top and bottom, labeled with numbers and letters like '15 NO', '22 NC', 'A1', '14 NO', '22 NC', 'A2', '2n', '4n', '6n'. A QR code is visible on the bottom left of the device.

### TeSys Deca Contactors

#### Technical Benefits

- Deca green delivers a consistent low consumption range of contactors from 9 A to 80 A.
- Covers control voltage from 24 to 250 V, with same coils for AC and DC.
- Designed to meet the requirements of industrial and HVAC applications
- With IEC60335-1 compliance, improved fire resistance, and dust-proof auxiliaries
- Suitable for safety applications thanks to mechanically linked contacts and mirror contacts
- Outstanding breaking/making capacity up to 20 In with PLC direct connection

Offer Marketing Illustration

Product benefits / Features



Technical Illustration

Assembly's dimensions

