


Specifications



LT6CT2001

Product availability: Non-Stock - Not normally stocked in distribution facility

Range	TeSys
Device short name	LT6CT
Product or Component Type	Current transformer
Range compatibility	TeSys TeSys T motor controller

Current transformer ratio	200/1
Accuracy class	Class 5P
Precision limit factor	15
[Ui] Rated Insulation Voltage	690 V
Diameter	1.4 in (35 mm)
Cable cross section	0.05 in² (30 mm²)
Height	4.2 in (107 mm)
Width	3.7 in (95 mm)
Depth	1.0 in (25 mm)
Product Weight	1.21 lb(US) (0.55 kg)

Standards	BS 7626 IEC 60185
Maximum ambient air temperature for operation	122 °F (50 °C)

Category	US1CTR521259
Discount Schedule	CTR5
GTIN	3389119405348
Returnability	No
Country of origin	GB

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.181 in (3.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	4.921 in (12.500 cm)
Package 1 Length	4.173 in (10.600 cm)
Package weight(Lbs)	15.873 oz (450.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	21.319 lb(US) (9.670 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	78b0d24c-0e62-4f91-9397-1958e4735328
EU RoHS Directive	Compliant By Exemption

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.