



Main

Range	TeSys
Device short name	LT6CT
Product or Component Type	Current transformer
Range compatibility	TeSys TeSys T motor controller

Complementary

Current transformer ratio	800/1
Accuracy class	Class 5P
Precision limit factor	15
[Ui] Rated Insulation Voltage	690 V
Diameter	0.39 in (10 mm)
Cable cross section	0.47 in ² (300 mm ²)
Height	4.21 in (107 mm)
Width	3.74 in (95 mm)
Depth	0.98 in (25 mm)
Net Weight	1.50 lb(US) (0.68 kg)

Environment

Standards	IEC 60185 BS 7626
Maximum ambient air temperature for operation	122 °F (50 °C)

Ordering and shipping details

Category	22338-SOLID STATE OVERLOAD RELAYS
Discount Schedule	I12
GTIN	3389110943283
Returnability	No
Country of origin	GB

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.000 cm)
Package 1 Width	4.92 in (12.500 cm)
Package 1 Length	4.17 in (10.600 cm)
Package 1 Weight	25.93 oz (735.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	14
Package 2 Height	5.91 in (15.000 cm)

Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	24.17 lb(US) (10.964 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------