

Product data sheet

Specifications



Short rear connections, ComPacT NSX, EasyPact CVS, 250A, set of 2 parts

LV429235

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	ComPacT NSX100...250 ComPacT NSX100...250 DC
Product or Component Type	Short rear connection
Accessory / separate part category	Connection accessory
Range compatibility	ComPacT ComPacT NSX100 ComPacT ComPacT NSX160 ComPacT ComPacT NSX250 ComPacT Compact NSX100 DC ComPacT Compact NSX160 DC ComPacT Compact NSX250 DC ComPacT EasyPact CVS100 ComPacT EasyPact CVS160 ComPacT EasyPact CVS250 ComPacT ComPacT INS ComPacT Compact INV
Poles description	3P 4P
Line Rated Current	250 A

Complementary

Location of connection	Rear
Shape	Short
Quantity per Set	Set of 2

Ordering and shipping details

Category	US10NET01081
Discount Schedule	0NET
GTIN	3606480019692
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.984 in (2.500 cm)
Package 1 Width	3.937 in (10.000 cm)
Package 1 Length	5.906 in (15.000 cm)
Package weight(Lbs)	5.848 oz (165.800 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	4.331 in (11.000 cm)
Package 2 Width	7.913 in (20.100 cm)
Package 2 Length	13.780 in (35.000 cm)
Package 2 Weight	4.828 lb(US) (2.190 kg)
Unit Type of Package 3	S04
Number of Units in Package 3	60
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	15.748 in (40.000 cm)
Package 3 Length	23.622 in (60.000 cm)
Package 3 Weight	23.475 lb(US) (10.648 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	83
Circularity Profile	No need of specific recycling operations
Take-back	No

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX

Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

