Product data sheet

Specifications

Short terminal shield, ComPacT NSX100/160/250, pitch 35mm, IP40, 4 poles

LV429516

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Short terminal shield
Range compatibility	ComPacT ComPacT NSX100 ComPacT ComPacT NSX160 ComPacT ComPacT NSX250 ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 ComPacT ComPacT NSX DC NSX100 DC ComPacT ComPacT NSX DC NSX160 DC ComPacT ComPacT NSX DC NSX250 DC ComPact Compact NSX100 DC ComPact Compact NSX160 DC ComPact Compact NSX250 DC EasyPact EasyPact CVS100 EasyPact EasyPact CVS160 EasyPact EasyPact CVS250
Accessory / Separate Part Type	Insulation accessories
Poles description	4P
Quantity per Set	1

Complementary

Connection pitch	1.4 in (35 mm)
IP degree of protection	IP40 conforming to IEC 60529
Product Compatibility	Circuit-breaker Plug-in base

Ordering and shipping details

Category	US10DE201103
Discount Schedule	0DE2
GTIN	3606480019906
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.378 in (3.500 cm)
Package 1 Width	3.150 in (8.000 cm)
Package 1 Length	5.906 in (15.000 cm)
Package weight(Lbs)	2.363 oz (67.000 g)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	7.540 lb(US) (3.420 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	19.685 in (50.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	54.851 lb(US) (24.880 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**0.5 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.3 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Product contains halogen above thresholds**
PVC free	**Yes**
Silicon free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**2**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Offer Marketing Illustration

Product benefits / Features