Product data sheet
Characteristics

LV432677
Circuit breaker, ComPact NSX400F, 36kA/415VAC, MicroLogic 2.3 trip unit 400A, 4 poles 4d

Main

Range	ComPact
Product name	ComPact NSX
Range of Product	ComPact NSX400...630
Device short name	NSX400F
Product or Component Type	Circuit breaker
Device Application	Distribution
Number of poles	4P
Protected poles description	4t 3t + N/2 3t
Neutral position	Left
Line Rated Current	400 A 104 °F (40 °C)
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network Frequency	50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	40 KA Icu 220/240 V AC 50/60 Hz IEC 60947-2 85 KA 240 V AC 50/60 Hz UL 508 25 KA Icu 500 V AC 50/60 Hz IEC 60947-2 36 KA Icu 380/415 V AC 50/60 Hz IEC 60947-2 10 KA Icu 660/690 V AC 50/60 Hz IEC 60947-2 35 KA 480 V AC 50/60 Hz UL 508 20 KA 600 V AC 50/60 Hz UL 508 20 KA Icu 525 V AC 50/60 Hz IEC 60947-2 30 kA Icu 440 V AC 50/60 Hz IEC 60947-2
Performance level	F 36 kA 415 V AC
Trip unit name	MicroLogic 2.3
Trip unit technology	Electronic
Trip unit protection functions	LSoI
Control Type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	40 KA 220/240 V AC 50/60 Hz IEC 60947-2 36 KA 380/415 V AC 50/60 Hz IEC 60947-2 10 KA 660/690 V AC 50/60 Hz IEC 60947-2 10 KA 525 V AC 50/60 Hz IEC 60947-2 25 KA 500 V AC 50/60 Hz IEC 60947-2 30 kA 440 V AC 50/60 Hz IEC 60947-2
Mechanical durability	15000 cycles
Electrical durability	3000 Cycles 690 V In 6000 Cycles 690 V In/2 6000 Cycles 440 V In 12000 cycles 440 V In/2
Mounting Support	Backplate

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Upside connection	Front
Downside connection	Front
Connection pitch	1.77 in (45 mm)
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	400 A 104 °F (40 °C)
Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	160...400 A
Long-time protection delay adjustment type tr	Fixed
[tr] long-time protection delay adjustment range	16 s 6 x Ir
Thermal memory	20 minutes before and after tripping
Short-time protection pick-up adjustment type Isd	Adjustable 9 settings
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Fixed
Instantaneous protection pick-up adjustment type Ii	Fixed
[Ii] instantaneous protection pick-up adjustment range	4800 A
Earth-leakage protection	Without
Neutral protection settings	0.5 x Ir 3t + N/2) 1 x Ir 4t) No protection 3t)
Zone selective interlocking ZSI	Without
Number of slots for electrical auxiliaries	6
Local signalling	For ready to operate flashing LED (green) For overload LED 105 % Ir (red) For overload LED 90 % Ir (orange)
Width (W)	7.28 in (185 mm)
Height (H)	10.04 in (255 mm)
Depth (D)	4.33 in (110 mm)
Net Weight	17.42 lb(US) (7.9 kg)

Environment

Standards	EN/IEC 60947
Product Certifications	CCC EAC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 IEC 62262
Ambient Air Temperature for Operation	-13…158 °F (-25…70 °C)
Ambient Air Temperature for Storage	-58…185 °F (-50…85 °C)
Relative humidity	0…95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000 m...5000 m with derating

Ordering and shipping details

Category	01101-NF..E COMPACT NS IEC CIRCUIT BREAKERS, SWITCHES & MCP'S
Discount Schedule	DE2
GTIN	3606480015083
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.87 in (14.913 cm)
Package 1 Width	7.96 in (20.219 cm)
Package 1 Length	11.40 in (28.96 cm)
Package 1 Weight	16.13 lb(US) (7.318 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	50.10 lb(US) (22.726 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months