

Product data sheet

Specifications



ULP wiring accessory, ComPacT NSX, NSX cord, 1.3m length, voltage below 480VAC

LV434201

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device short name	cord L = 1.3 m
Product or Component Type	Terminal block connector
Range compatibility	ComPact ComPact NSX DC PowerPact PowerPact Multistandard ComPact ComPact NSX

Complementary

Mounting Mode	By clips
Location of connection	Inside
Localisation on device	Internal
Connector Type	1 RJ45
[Ue] rated operational voltage	<= 480 V
Length	4.3 ft (1.3 m)

Ordering and shipping details

Category	US10DE201103
Discount Schedule	0DE2
GTIN	3606480022241
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.299 in (3.300 cm)
Package 1 Width	2.165 in (5.500 cm)
Package 1 Length	4.567 in (11.600 cm)
Package weight(Lbs)	2.335 oz (66.200 g)
Unit Type of Package 2	S02
Number of Units in Package 2	46
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Weight	7.374 lb(US) (3.345 kg)
------------------	-------------------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	79a90f7d-128a-434a-bffd-1c1b94bd59b4
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	4
Circularity Profile	End of Life Information
Take-back	No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.