

Product data sheet

Specifications



TeSys F - contactor coil - LX4F8 - 380...400V DC

LX4F8QW

 To be discontinued on: Dec 31, 2028

 To be discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4F8
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F800
Control circuit type	DC low consumption
[Uc] control circuit voltage	380...400 V DC
Operating time	40...50 ms opening 60...80 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	600 cyc/h 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational: 0.85...1.1 Uc (at 55 °C) Drop-out: 0.3...0.5 Uc (at 55 °C)
Inrush power in W	1900 W (at 20 °C)
Hold-in power consumption in W	12 W at 20 °C

Environment

Ambient air temperature for operation	-5...55 °C
Net weight	1.65 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	12.000 cm
Package 1 Length	22.500 cm
Package 1 Weight	1.378 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.767 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	70
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No