

Product data sheet

Specifications



TeSys F - contactor coil - LX4FL - 250 V DC

LX4FL250

 **Discontinued on:** Aug 15, 2025

Product availability: Non-Stock - Not normally stocked in distribution facility

 **Discontinued**

Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX4FL
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F630 LC1F1250
Control circuit type	DC low consumption
[Uc] control circuit voltage	250 V DC
Inductance of closed circuit	815 H
Average resistance	38 Ohm inrush 68 °F (20 °C) 6080 Ohm holding 68 °F (20 °C)
Operating time	40...50 ms opening 60...70 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1200 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out 0.2...0.35 Uc 131 °F (55 °C)) Operational 0.85...1.1 Uc 131 °F (55 °C))
Inrush power in W	1600 W 68 °F (20 °C))
Hold-in power consumption in W	9 W 68 °F (20 °C)

Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	3.20 lb(US) (1.45 kg)

Ordering and shipping details

Category	US1CP1018401
Discount Schedule	CP10
GTIN	3389110247350
Returnability	No
Country of origin	CZ

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.9 in (9.8 cm)
Package 1 Width	4.5 in (11.4 cm)
Package 1 Length	8.9 in (22.5 cm)
Package weight(Lbs)	3.20 lb(US) (1.45 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	70
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No