

Product data sheet

Specifications



Coil for Tesys LC1F

LX5FKW25

Main

Control circuit type	DC wide range
[Uc] control circuit voltage	110 V DC
Mechanical durability	1 Mcycles
Maximum operating rate	60 cyc/h 70 °C

Complementary

Control circuit voltage limits	Drop-out: 0.3...0.45 Uc (at 70 °C) Operational: 0.8...1.25 Uc (at 70 °C)
--------------------------------	---

Environment

Ambient air temperature for operation	-55...70 °C
Quantity per set	Set of 2 (coil with resistors)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 cm
Package 1 Width	14.5 cm
Package 1 Length	22.5 cm
Package 1 Weight	1.42 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No