


Product data sheet

Specifications



TeSys F - specific contactor coil - 240 V AC 40...400 Hz low consumption

LX9FG240

 To be discontinued on: Dec 31, 2028

 To be discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or Component Type	Specific contactor coil
Device short name	LX9FG
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F185 LC1F225
Control circuit type	AC 40...400 Hz low consumption
[Uc] control circuit voltage	240 V AC 40...400 Hz
Inductance of closed circuit	7.22 H
Average resistance	50.6 Ohm inrush 68 °F (20 °C) 2060 Ohm holding 68 °F (20 °C)
Operating time	130 ms opening 35 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C)) Drop-out 0.2...0.55 Uc 131 °F (55 °C))
Inrush power in VA	950...1180 VA 40...400 Hz (at 68 °F (20 °C))
Hold-in power consumption in VA	8.9...10.9 VA 40...400 Hz (at 68 °F (20 °C))
Heat dissipation	8...9.8 W

Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	1.21 lb(US) (0.55 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110084030

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.0 in (7.5 cm)
Package 1 Width	4.1 in (10.5 cm)
Package 1 Length	7.0 in (17.7 cm)
Package weight(Lbs)	20.6 oz (585.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	14
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	19.039 lb(US) (8.636 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	70
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No