

Product data sheet

Specifications



TeSys F - specific contactor coil - 220 V DC low consumption

LX9FL931

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Product or Component Type	Specific contactor coil
Device short name	LX9FL
Range compatibility	TeSys TeSys F LC1F contactor TeSys TeSys F DR2S resistor
Product Compatibility	DR2SC LC1F630
Control circuit type	AC 40...400 Hz low consumption DC low consumption
[Uc] control circuit voltage	220...240 V DC
Inductance of closed circuit	3.6 H
Average resistance	64.5 Ohm inrush 68 °F (20 °C) 518 Ohm holding 68 °F (20 °C)
Operating time	60 ms opening 20 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1800 cyc/h 158 °F (70 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C)) Drop-out 0.3...0.5 Uc 131 °F (55 °C))
Inrush power in W	733 W 68 °F (20 °C))
Hold-in power consumption in W	48 W 68 °F (20 °C)
Heat dissipation	22.8...27.8 W

Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	3.20 lb(US) (1.45 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110248661
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	CZ
-------------------	----

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.06 in (10.3 cm)
Package 1 Width	4.5 in (11.5 cm)
Package 1 Length	8.9 in (22.6 cm)
Package weight(Lbs)	3.258 lb(US) (1.478 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	20.514 lb(US) (9.305 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No