

Product data sheet

Specifications



LXM52 single drive 6A/18A

LXM52DD18C41000

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Device short name	LXM 52
Product or Component Type	Single drive
Product compatibility	Servo motor SHS Servo motor SH3 2.8 in (70 mm), 3 optimized in terms of torque and speed Servo motor SH3 3.9 in (100 mm), 1 optimized in terms of torque and speed Servo motor SH3 3.9 in (100 mm), 2 optimized in terms of torque and speed Servo motor SH3 3.9 in (100 mm), 3 optimized in terms of high torque Servo motor SH3 5.5 in (140 mm), 1 optimized in terms of high torque Servo motor MH3 3.9 in (100 mm), 2 optimized in terms of torque and speed
Component name	LXM52

Complementary

Phase	Three phase
[Us] rated supply voltage	208...480 V - 15...10 %
Supply frequency	50...60 Hz - 5...5 %
Continuous output current	6 A 8 kHz
Output current 3s peak	18 A
Continuous power	3.3 kW
Nominal power	1.8 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal 0.75...5.3 mm², 18 AWG...10 AWG CN1)
Tightening torque	CN1 6.02 lbf.in (0.68 N.m)
Number of inputs	4 digital
Discrete input voltage	24 V DC
Number of outputs	2 digital
Discrete output voltage	24 V DC
Contact bounce time	> 1 ms compliment of STO_A, compliment of STO_B
Communication interface	SERCOS III, Integrated
Width	1.9 in (48 mm)
Height	10.6 in (270 mm)
Depth	8.5 in (217 mm)
Product Weight	4.2 lb(US) (1.9 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	UL 508C IEC 61800-3
Product Certifications	CE
IP degree of protection	IP20 IEC 60721-3-3
Vibration resistance	10 m/s² conforming to IEC 60721-3-3
Shock resistance	100 m/s² IEC 60721-3-3
Pollution degree	2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...95 %
Ambient Air Temperature for Operation	32...122 °F (0...50 °C)

Ordering and shipping details

Category	US1PC5218355
Discount Schedule	PC52
GTIN	3606480517310
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.346 in (8.500 cm)
Package 1 Width	10.827 in (27.500 cm)
Package 1 Length	12.992 in (33.000 cm)
Package weight(Lbs)	5.505 lb(US) (2.497 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	3
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	17.968 lb(US) (8.150 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	24
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	165.073 lb(US) (74.876 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 148 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	23 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 123 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	3d0be293-7e12-47d2-b52f-e501202c4302
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No