


# Product data sheet

Specifications

## Multi9 - comb busbar - 3L - 18 mm pitch - 12 modules - 115A



M9XUP312

**Product availability: Stock - Normally stocked in distribution facility**

### Main

|                                    |                                                                            |
|------------------------------------|----------------------------------------------------------------------------|
| Range                              | Multi9                                                                     |
| Product or Component Type          | Comb busbar                                                                |
| Mounting Mode                      | Horizontal                                                                 |
| Accessory / separate part category | Connection accessory                                                       |
| Lines description                  | 3L                                                                         |
| Length in 18 mm modules            | 12                                                                         |
| Standards                          | UL 489<br>UL 508<br>CSA C22.2 No 5<br>CSA C22.2 No 14-13<br>EN/IEC 61439-1 |
| Product certifications             | CULus                                                                      |

### Complementary

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Number of ways                 | 3 ways 3 L                                        |
| Distribution type              | L1 L2 L3                                          |
| Poles configuration for 1 way  | 1 x 3P                                            |
| Connection pitch               | 0.7 in (18 mm)                                    |
| Connector type                 | tooth                                             |
| Distance between way           | 2.1 in (54 mm)                                    |
| Insulation                     | Insulated                                         |
| Device presentation            | Uncuttable                                        |
| [Ie] rated operational current | 115 A 104 °F (40 °C)                              |
| [Ue] rated operational voltage | 480 V AC 50/60 Hz Ph/Ph<br>277 V AC 50/60 Hz Ph/N |
| [Ui] rated insulation voltage  | 1000 V AC 50/60 Hz UL 508                         |
| Mounting location              | Top tunnel type terminals                         |
| 9 mm pitches                   | 24                                                |
| Width                          | 8.5 in (216 mm)                                   |
| color                          | Light gray RAL 7035)                              |
| Range compatibility            | Multi9 C60BP                                      |

### Environment

|                 |                                       |
|-----------------|---------------------------------------|
| Fire resistance | 1760 °F (960 °C) 30 s ) IEC 60695-2-1 |
|-----------------|---------------------------------------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                         |                                       |
|-------------------------|---------------------------------------|
| Pollution degree        | 3                                     |
| IP degree of protection | IP20 with end-pieces and tooth covers |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10DE200949  |
| Discount Schedule | 0DE2          |
| GTIN              | 3606481192844 |
| Returnability     | Yes           |
| Country of origin | MK            |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Nbr. of units in pkg.        | 1                        |
| Package 1 Height             | 0.787 in (2.000 cm)      |
| Package 1 Width              | 2.165 in (5.500 cm)      |
| Package 1 Length             | 8.268 in (21.000 cm)     |
| Package weight(Lbs)          | 5.891 oz (167.000 g)     |
| Unit Type of Package 2       | S02                      |
| Number of Units in Package 2 | 50                       |
| Package 2 Height             | 5.906 in (15.000 cm)     |
| Package 2 Width              | 11.811 in (30.000 cm)    |
| Package 2 Length             | 15.748 in (40.000 cm)    |
| Package 2 Weight             | 19.244 lb(US) (8.729 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 4 kg CO2 eq.                                  |
| Carbon footprint of the manufacturing phase [A1 to A3] | 0.8 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 3 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.4 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                                                                                                                                               |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | No                                                                                                                                                                                                                                                            |
| Packaging without single use plastic   | No                                                                                                                                                                                                                                                            |
| SCIP Number                            | 12618b2a-bc0e-4c2d-bb7b-9185c26e01fe                                                                                                                                                                                                                          |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                                                                                                                                                                                                     |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                                                                                                                                        |
| California proposition 65              | WARNING: This product can expose you to chemicals including: DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| PVC free                               | Yes                                                                                                                                                                                                                                                           |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 67                                                                                                                                                                                                               |
| Circularity Profile           | No need of specific recycling operations                                                                                                                                                                         |
| Take-back                     | No                                                                                                                                                                                                               |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |