

Product data sheet

Specifications



PowerLogic EM3500 DIN rail meter - BACnet - current transformer

METSEEM3560

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PowerLogic
range of product	PowerLogic EM3500
Device short name	EM3560
Product or Component Type	Energy meter
Metering type	Current I1, I2, I3, Iavg Voltage U21, U32, U13, V1, V2, V3 Peak demand power PM, QM, SM Demand power P, Q, S

Complementary

Poles description	3P + N
Type of measurement	Active and reactive power total Active and reactive power per phase Apparent power total Apparent power per phase Power factor total Power factor per phase Peak demand power Current Voltage Frequency
Device Application	Partial meter Sub billing
Accuracy class	Class 0.2S power IEC 62053-22 Class 0.2S energy IEC 62053-22 Class 0.2S power ANSI C12.20 Class 0.2S energy ANSI C12.20
Measurement accuracy	Power +/- 0.2 % Energy +/- 0.2 %
input type	Low voltage current transformer 0.333 V or 1 V
Rated voltage	90...347 V
Network frequency	60 Hz 50 Hz
Technology Type	Electronic
Display Type	Backlit LCD
Measurement current	5...32000 A
Display digits	5

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Information displayed	Status and alert Communication with system Input/output status Error Tx activity Rx activity Instant power per usage
Tamperproof of settings	Protected by access code
Communication port protocol	BACnet MS/TP 9600 bauds...115200 bauds (automatic detection) - 2-wire
Communication port support	Screw terminal block RS485
Communication Service	Total cumulated energy Total cumulated active energy
Data recording	Energy consumption logs
Demand intervals	Fixed or rolling block External synchronisation to communication
Local signalling	Red LED threshold reached Green flashing LED output signal
number of accumulator inputs	1 pulse
Number of Outputs	1 alarm output
Buffer size	32-bit 3
[Ue] rated operational voltage	90...347 V AC 50/60 Hz between phase and neutral UL 156...600 V AC 50/60 Hz between phases UL 90...300 V AC 50/60 Hz between phase and neutral CE 125...300 V DC
Power consumption in VA	5 VA 347 V AC between phase and neutral) 5 VA 600 V AC between phases)
Power consumption in W	3 W 300 V
Ride-through time	100 ms 120 V AC
Mounting Mode	Clip-on By screws
Mounting Support	DIN rail
Standards	UL 508 CSA C22.2 No 14-05 IEC 61010-1
Product certifications	CE conforming to IEC 61010 CULus conforming to UL 508

Environment

Relative humidity	0...95 %
Ambient air temperature for operation	-22...158 °F (-30...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Color	Dark grey
9 mm pitches	12
Width	4.2 in (107 mm)
Height	3.6 in (91 mm)
Depth	2.3 in (59 mm)

Ordering and shipping details

Category	US10PL109798
----------	--------------

Discount Schedule	0PL1
GTIN	3606487732723
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.6 in (9.1 cm)
Package 1 Width	4.2 in (10.7 cm)
Package 1 Length	2.3 in (5.9 cm)
Package weight(Lbs)	8.0006 lb(US) (3.629 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	11 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.9 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	7e026619-91b4-4741-a9c3-c4a1c1c83d61
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	0
Circularity Profile	End of Life Information
Take-back	No