

Product data sheet

Specifications



Power quality meter, PowerLogic ION7400, Standard, transducer, 512 MB, 256 s/c

METSEION7413

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PowerLogic
Product name	PowerLogic ION7400
Product or Component Type	Power meter
Device short name	ION7413
model type	Standard

Complementary

Power quality analysis	EN 50160 2010 compliance report IEEE 519 2014 compliance report IEC 61000-4-30 class S power quality measurement up to the 63rd harmonic harmonic distortion waveform capture voltage sag and swell detection programmability (logic and math functions) IEC 62586 power quality monitoring IEC 61000-4-15 disturbance direction detection rapid voltage change
Device Application	WAGES metering Power monitoring Data aggregation Revenue billing
Type of measurement	Current Voltage Frequency Active and reactive power total Apparent power total Power factor total Active and reactive power per phase, rms Apparent power per phase, rms Power factor per phase, rms Active and reactive energy Apparent energy
supply voltage	20...60 V DC +/- 10 %
Network Frequency	50 Hz 60 Hz
Line Rated Current	10 A 1 A 5 A
Poles description	1P + N 3P 3P + N
Power Consumption in W	17 W
Display Type	Without Display
Sampling rate	256 samples/cycle

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Measurement current	50...10000 mA
Analogue input type	Voltage (impedance 5 MOhm) Current (impedance 0.3 mOhm)
Measurement voltage	57...400 V AC 42...69 Hz between phase and neutral 100...690 V AC 42...69 Hz between phases
Frequency measurement range	42...69 Hz
Number of inputs	3 digital 30 V AC 3 digital 60 V DC
Measurement accuracy	Current +/- 0.1 % Voltage +/- 0.1 % Active energy +/- 0.2 %
Accuracy class	Class 0.2S active energy IEC 62053-22 Class 0.2 active energy ANSI C12.20 Class 0.2 active power IEC 61557-12 Class 0.5S reactive energy IEC 62053-24 Class 0.5 power factor IEC 61557-12 Class 0.2 voltage IEC 61557-12 Class 0.2 current IEC 61557-12 Class 0.2 frequency IEC 61557-12 Class 0.2 active energy IEC 61557-12
Number of Outputs	1 pulse
Information displayed	Voltage Current Frequency Power Energy consumption Harmonic distortion
Communication port protocol	Modbus RTU 115 kbauds - 2-wire ION 115 kbauds - 2-wire DNP3 IEC 61850 Modbus TCP/IP Ethernet Modbus TCP/IP daisy chain 10/100 Mbit/s RSTP 801.1d 2004 DLMS
Communication port support	ETHERNET Screw terminal block RS485 Mini B USB USB
Communication Network Type	IPv6 (internet protocol)
Data recording	Sequence of event recording Trending/forecasting Harmonics logs Time stamping GPS synchronisation Waveform logs Min/max of instantaneous values Sag and swell logs Data logs Event logs Alarm logs 50 data recorders
Memory capacity	512 MB
Web services	Customizable home page File upload/download via FTP File upload/download via SFTP Web server Alarm notification by e-mail Viewing of captured waveform (FTP) Viewing of captured waveform (web) HTTPS server

Communication Service	NTP time synchronization SMTP e-mail notification RSTP support DHCP SNMP PTP time synchronization
Cybersecurity	Enable/disable communication ports Robust security logs Port hardening Password protection Syslog protocol support
Mounting Mode	Clip-on
Mounting support	DIN rail
Type of Installation	Indoor installation
Installation category	III
Safety Construction	III400...690 V conforming to IEC 61010-1:ed. 3 III400...690 V conforming to EN 61010-1:ed. 3 III347...600 V conforming to UL 61010-1:ed. 3 III347...600 V conforming to CSA C22.2 No 61010-1:ed. 3
Standards	IEC 61326-1 IEC 62053-22 IEC 62053-24 IEC 62052-11 IEC 61557-12 IEEE 1588 IEC 62586
Product certifications	CE CULus N998
Width	3.6 in (90.5 mm)
Depth	3.6 in (90.8 mm)
Height	3.6 in (90.5 mm)
Product Weight	18.6 oz (528 g)

Environment

Electromagnetic compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Immunity to impulse waves conforming to IEC 61000-4-12 Conducted and radiated emissions conforming to EN 55022 Conducted and radiated emissions conforming to EN 55011 Conducted and radiated emissions conforming to FCC part 15 Conducted and radiated emissions conforming to ICES-003 Conducted RF disturbances (2...150 Hz) conforming to CLC/TR 50579 Surge withstand conforming to IEEE C37.90.1
IP degree of protection	IP30 conforming to IEC 60529
Relative humidity	5...95 %
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	US10PM109753
----------	--------------

Discount Schedule	0PM1
GTIN	3606481384584
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.512 in (14.000 cm)
Package 1 Width	5.512 in (14.000 cm)
Package 1 Length	7.283 in (18.500 cm)
Package weight(Lbs)	2.271 lb(US) (1.030 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	14.597 lb(US) (6.621 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	17.717 in (45.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	143.230 lb(US) (64.968 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	244 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	39 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	203 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	23a3df3b-8f68-444e-b6b0-c97b248da7da
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	12
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.