


Product data sheet

Specifications



Cable entry membrane, PanelSeT, PanelSeT, type FL21 with 25 entrances IP66

NSYAECPFLT25

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Cable entry membrane
Accessory / separate part category	Cable management accessory
Device Application	Multi-purpose
Range compatibility	PanelSeT S3D compact enclosure PanelSeT CRN compact enclosure PanelSeT SF suitable enclosure
Device composition	1 membrane 1 fixing elements
Quantity per Set	Set of 1

Complementary

Mounting Support	Cable gland plate
Material	TPE (thermoplastic elastomer)
Fixing mode	By fixing element
Total cable entry number	25
Cable entry number	4 x 0.2...0.3 in (5...7 mm) 4 x 0.3...0.5 in (8...12 mm) 4 x 0.6...0.8 in (14...20 mm) 12 x 0.4...0.6 in (10...14 mm) 1 x 0.8...1.02 in (20...26 mm)
Height	1.2 in (30 mm)
Width	External: 8.4 in (214 mm) Fixing center: 7.6 in (194 mm)
Depth	Fixing center : 2.4 in (62 mm) External : 3.5 in (88 mm)
color	Gray RAL 7035)
Product Weight	0.71 lb(US) (0.32 kg)

Environment

IP degree of protection	IP66
Flame retardance	V0 conforming to UL 94
Ambient Air Temperature for Operation	-40...212 °F (-40...100 °C)
Environmental characteristic	Oil resistant UL 157 FIMKO UV resistant Weatherproof Fire resistance UL 94 V0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480169052
Returnability	No
Country of origin	FI

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.984 in (2.500 cm)
Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	8.661 in (22.000 cm)
Package weight(Lbs)	10.653 oz (302.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	7.874 in (20.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	11.811 in (30.000 cm)
Package 2 Weight	13.982 lb(US) (6.342 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	400
Package 3 Height	28.346 in (72.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	279.987 lb(US) (127.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No