

Product data sheet

Specifications



outlet grille plast cut out 92x92mm
ext dim 137x117mm IP54

NSYCAG92LPF

Product availability: Stock - Normally stocked in distribution facility

Main

Range	ClimaSys
Product	ClimaSys CA
Range compatibility	Prisma Prisma P ClimaSys ClimaSys CV fan
Certification	CSA
Product or Component Type	Outlet grille
Accessory / separate part category	Thermal management accessory
Accessory / separate part destination	ClimaSys ventilation system
Fixing Mode	By screws Clipped
Device composition	1 external part front 1 support frame 1 G2 M1 synthetic standard filter rear of outlet grille

Complementary

Material	Injected thermoplastic (ASA PC)
color	External part Gray RAL 7035)
Cut-out dimensions	92 x 92 mm
Height	External: 5.4 in (137 mm)
Width	External: 4.6 in (117 mm)
Depth	External : 0.5 in (13 mm)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151521
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.575 in (4.000 cm)
Package 1 Width	4.921 in (12.500 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	5.709 in (14.500 cm)
Package weight(Lbs)	5.256 oz (149.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	102
Package 2 Height	15.748 in (40.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	33.506 lb(US) (15.198 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	816
Package 3 Height	35.827 in (91.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	296.742 lb(US) (134.600 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	8
Circularity Profile	No need of specific recycling operations
Take-back	No