

Product data sheet

Specifications



Climasys CC - electronic hygrostat - 200â€¦240 V - Hr 20â€¦80% - OLED screen

NSYCCOHY230VID

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ClimaSys
Product name	ClimaSys CC
Product or Component Type	Electronic hygrostat
Humidity setting range	20...80 %
Display Type	OLED screen
Information Displayed	Relative humidity

Complementary

Input voltage	200...240 V AC
Maximum switching capacity	4 A 230 V AC
Electrical connection	6 terminals 2.5 mm²
Mounting Mode	By screws Clipped
Height	External: 3.3 in (85 mm)
Width	External: 2.2 in (56 mm)
Depth	External : 1.7 in (44 mm)
Mounting Location	On mounting plate Cross rails 35 mm DIN rail Spacial upright
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)
Hysteresis	3 %
Number of outputs	2 heating function
Material	PC
Color	Light gray
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product Certifications	UR

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480152634
Returnability	No
Country of origin	CN

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.283 in (5.800 cm)
Package 1 Width	2.953 in (7.500 cm)
Package 1 Length	3.425 in (8.700 cm)
Package weight(Lbs)	5.432 oz (154.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	75
Package 2 Height	10.630 in (27.000 cm)
Package 2 Width	11.929 in (30.300 cm)
Package 2 Length	17.717 in (45.000 cm)
Package 2 Weight	25.463 lb(US) (11.550 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	900
Package 3 Height	36.614 in (93.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	330.694 lb(US) (150.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	3452f1a3-f13d-4adf-84ba-2572bcc8e35c
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.