# Product data sheet
## Characteristics

# NSYCRNG106400T
## Spacial CRNG tspt door w/o mount.plate. H1000xW600xD400 IP66 IK08 RAL7035.

## Main

| | |
|---|---|
| Range | Spacial |
| Product name | Spacial CRNG |
| Application | Multi-purpose |
| Category | Compact enclosure |
| Enclosure nominal height | 39.37 in (1000 mm) |
| Enclosure nominal width | 23.62 in (600 mm) |
| Enclosure nominal depth | 15.75 in (400 mm) |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body<br>1 cable gland plate<br>1 door<br>1 lock |
| Door type | Glass |
| Mounting plate description | Without mounting plate |

## Complementary

| | |
|---|---|
| Body type | Single piece body |
| Number of doors | Front face 1 |
| Door opening side | Reversible 120 °) |
| Lock type | 3 points lock, 5 mm double-bar |
| Type of gland plate | Standard |
| Accessibility for operation | Front |
| Removable parts | Door by hinges<br>Cable gland plate by screws |
| Material | Body steel<br>Door steel and security glass |
| Surface finish | Epoxy-polyester powder |
| Color | Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | CUL<br>UL |
| Net Weight | 80.25 lb(US) (36.4 kg) |

## Environment

| | |
|---|---|
| IP degree of protection | IP55 IEC 60529 |
| IK degree of protection | IK08 IEC 62262 |

## Ordering and shipping details

| | |
|---|---|
| Category | 80034-ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule | ES1 |
| GTIN | 3606480298141 |
| Returnability | No |
| Country of origin | FR |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.72 in (45.0 cm) |
| Package 1 Width | 24.02 in (61.0 cm) |
| Package 1 Length | 40.16 in (102.0 cm) |
| Package 1 Weight | 64.29 lb(US) (29.16 kg) |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 78.35 in (199.0 cm) |
| Package 2 Width | 39.37 in (100.0 cm) |
| Package 2 Length | 47.24 in (120.0 cm) |
| Package 2 Weight | 414.47 lb(US) (188.0 kg) |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |