

Product data sheet

Specifications



Climasys forced vent. 170 m3/h, 230V without grille

NSYCVF170M230

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Range compatibility	Prisma P
Flow rate	Free flow rate: 44910.05 Gal/hr(US) (170 m3/h) at 50 Hz
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	17 W
Noise level < at	41 dB
Height	External: 4.7 in (119 mm)
Width	External: 4.7 in (119 mm)
Depth	External : 1.5 in (38 mm)
Product Weight	1.81 lb(US) (0.82 kg)
Material	Protective grille steel
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 fixing collar

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151422
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.362 in (6.000 cm)
Package 1 Width	5.906 in (15.000 cm)
Package 1 Length	6.693 in (17.000 cm)
Package weight(Lbs)	29.841 oz (846.000 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	7.874 in (20.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	11.811 in (30.000 cm)
Package 2 Weight	19.740 lb(US) (8.954 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	320
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	661.387 lb(US) (300.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 032 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 023 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	64
Circularity Profile	End of Life Information
Take-back	No



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



