

Product data sheet

Specifications



Climasys forced vent. 54 m3/h,
230V, 2 metal grilles and 2 anti-
insect filters

NSYCVF54M230MM2

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Anti-insect
Flow rate	Free flow rate without filter or grille: 44910.05 Gal/hr(US) (170 m3/h) Overall flow rate: 14265.5 Gal/hr(US) (54 m3/h) at 50 Hz
Input voltage	230 V 50/60 Hz

Complementary

Height	External: 4.7 in (120 mm)
Width	External: 4.7 in (120 mm)
Depth	External : 1.5 in (38 mm)
Cut-out dimensions	96 x 96 mm
Material	Outlet grille steel Filter stainless steel 304L
color	Outlet grille Gray RAL 7035)
IP degree of protection	IP33
Device composition	1 axial motor 1 power cord 2 anti-insect filter 2 metal louver

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151415
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.693 in (17.000 cm)
Package 1 Width	5.906 in (15.000 cm)
Package 1 Length	2.756 in (7.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	2.282 lb(US) (1.035 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	7.874 in (20.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	24.097 lb(US) (10.930 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Height	31.496 in (80.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	773.603 lb(US) (350.900 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	1 034 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 023 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes
Silicon free	Yes

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	64
Circularity Profile	End of Life Information
Take-back	No



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

