

Product data sheet

Specifications



ClimaSys forced vent. roof, 575m3/h, 230V, with roof outlet grille and filter G2, grey (RAL 7035)

NSYCVF575M230MF

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Top hood with fan
Range compatibility	Prisma Prisma P Prisma Prisma PH Prisma Prisma iPM M Acti 9 enclosure
Type of filter	G2
Flow rate	With outlet grille cut-out 291 x 291 mm: 92461.9 Gal/hr(US) (350 m3/h) Free flow rate: 151901.7 Gal/hr(US) (575 m3/h) at 50 Hz
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	85 W
Noise level < at	64 dB
Height	External: 3.8 in (96 mm)
Width	External: 13.4 in (340 mm)
Depth	External : 13.4 in (340 mm)
Cut-out dimensions	228 x 228 mm
Material	Hood steel
color	Hood Gray RAL 7035)
IP degree of protection	IP54
Device composition	1 hood top of enclosure 1 fan 1 fixing elements

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151392
Returnability	No
Country of origin	IT

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package 1 Height	4.724 in (12.000 cm)
Package 1 Width	13.780 in (35.000 cm)
Package 1 Length	13.780 in (35.000 cm)
Package weight(Lbs)	13.373 lb(US) (6.066 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	60
Package 2 Height	40.551 in (103.000 cm)
Package 2 Width	47.244 in (120.000 cm)
Package 2 Length	41.339 in (105.000 cm)
Package 2 Weight	831.143 lb(US) (377.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	5 178 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	39 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	12 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.7 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 116 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	9 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	64
Circularity Profile	End of Life Information
Take-back	No



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.