

Product data sheet

Specifications



Climasys forced vent. 65 m3/hour, 115V, with outlet grille plastic and filter

NSYCVF65M115PF

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate without filter or grille: 44910.05 Gal/hr(US) (170 m3/h) Free flow rate with standard filter: 17171.5 Gal/hr(US) (65 m3/h) at 50 Hz
Input voltage	115 V 50/60 Hz

Complementary

Height	External: 4.9 in (124 mm)
Width	External: 4.9 in (124 mm)
Depth	External : 2.2 in (55 mm)
Cut-out dimensions	Ø 108 mm
Material	Outlet grille ABS (acrylonitrile butadiene-styrene) Filter polyurethane foam
color	Outlet grille Black Filter Black
IP degree of protection	IP20
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151385
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.441 in (6.200 cm)
Package 1 Width	6.496 in (16.500 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	5.827 in (14.800 cm)
Package weight(Lbs)	26.914 oz (763.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	7.874 in (20.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	11.811 in (30.000 cm)
Package 2 Weight	17.320 lb(US) (7.856 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	563.678 lb(US) (255.680 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 332 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 324 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	64
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.