

Product data sheet

Specifications



Metal industrial cut-out box - low plain cover - H105xW105xD49 - IP55 - grey

NSYDB1010M

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	PanelSeT SDB
Device Application	Multi-purpose
Product or Component Type	Junction box
Enclosure Type	Empty enclosure
Type of front cover	Low plain cover
color	Light gray RAL 7035)

Complementary

Enclosure nominal height	4.1 in (105 mm)
Enclosure nominal width	4.1 in (105 mm)
Enclosure nominal depth	1.9 in (49 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 1 cover screw
Cable entry number	3 0.8 in (20.5 mm) M20) 3 1.004 in (25.5 mm) M25)
Cover fixing	Screw
Material	steel
Surface Finish	Epoxy-polyester powder
Product Weight	0.602 lb(US) (0.273 kg)

Environment

Standards	IEC 62208
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK07 conforming to IEC 62262

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480187766
Returnability	No
Country of origin	IN

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.165 in (5.500 cm)
Package 1 Width	4.331 in (11.000 cm)
Package 1 Length	4.528 in (11.500 cm)
Package weight(Lbs)	8.325 oz (236.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	5.118 in (13.000 cm)
Package 2 Width	9.252 in (23.500 cm)
Package 2 Length	11.220 in (28.500 cm)
Package 2 Weight	5.203 lb(US) (2.360 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	960
Package 3 Height	47.244 in (120.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	529.110 lb(US) (240.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	96
Circularity Profile	No need of specific recycling operations
Take-back	No

Offer Marketing Illustration

Product benefits / Features



Watertightness IP55
Robustness IK07



Metal
junction
boxes



Directly wall-mounted



Image of product in real life situation

