

Product data sheet

Specifications



Cable entry system type Multi-CS dimensions 112 x 36 mm and 12 openings

NSYDCD2412

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range	PanelSeT
Product or Component Type	Cable entry
Accessory / separate part category	Cable management accessory
Application	Multi-purpose
Mounting Location	Enclosure bottom
Cable entry	12 grommets 0.08...0.5 in (2...12 mm)
Quantity per Set	Set of 1
Material	polypropylene

Complementary

Height	5.8 in (148 mm)
Width	2.3 in (58 mm)
Depth	0.7 in (18 mm)
Product Weight	0.452 lb(US) (0.205 kg)
Cut-out dimensions	112 x 36 mm

Environment

resistance to chemical agents	Good resistant to alcohols Good resistance to mineral oils and greases Good resistance to weak acids and bases Good resistance to fuels
Flame retardance	V0 conforming to UL 94
Ambient Air Temperature for Operation	-22...212 °F (-30...100 °C)
IP degree of protection	IP65 IEC 60529

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606489429027
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package 1 Height	4.724 in (12.000 cm)
Package 1 Width	2.362 in (6.000 cm)
Package 1 Length	8.071 in (20.500 cm)
Package weight(Lbs)	6.772 oz (192.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	7.874 in (20.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	4.912 lb(US) (2.228 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Height	33.465 in (85.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	173.813 lb(US) (78.840 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	73e923a6-870d-4d0d-9a27-5e8c9bbeb14d
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No