

Product data sheet

Specifications

Cylindrical barrel reinforced keylock



NSYINKR2

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Accessory / separate part category	Locking accessory
Product or Component Type	Cylindrical barrel
Application	Multi-purpose
Mounting Support	Handle
Product Compatibility	SF, SM and PLA enclosures
Range compatibility	PanelSeT SF PanelSeT SM PanelSeT SD PanelSeT PLA
Device composition	1 cylindrical barrel 1 key

Complementary

Quantity per Set	Set of 1
------------------	----------

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480064968
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.984 in (2.500 cm)
Package 1 Width	2.362 in (6.000 cm)
Package 1 Length	3.150 in (8.000 cm)
Package weight(Lbs)	6.173 oz (175.000 g)
Unit Type of Package 2	PAM
Number of Units in Package 2	500
Package 2 Height	18.898 in (48.000 cm)
Package 2 Width	39.370 in (100.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	220.462 lb(US) (100.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	52da316e-d4e1-4114-85c0-32a03b2934fd
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No