

Product data sheet

Specifications

Multi-fixing LED lamp with socket Schuko - 230 V AC - 10W



NSYLAMLDS

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or Component Type	Lamp
Device Application	Multi-purpose
Device composition	1 lamp 1 fixing elements
Power factor	0.9

Complementary

Outlet standard deviation	Schuko
Rated lamp wattage	10 W
[Ue] rated operational voltage	230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control Type	Built-it switch
Luminous flux	950 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 9.8 ft (3 m) not supplied Cable quick connector 3.3 ft (1 m) not supplied
Mounting Support	Bracket DIN rail Metal parts
Fixing Mode	Clip-in Magnetic fixing Screws
Range compatibility	Spacial PanelSeT
Material	PC (UL94 V-0)
Length	14.6 in (372 mm)
Height	2.5 in (63 mm)
Width	1.6 in (40 mm)
color	Black RAL 9005)

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP degree of protection	IP20 conforming to IEC 60529
Electrical Insulation Class	Class I
Electromagnetic compatibility	EMC immunity EN 55015
Standards	UL 1598 IEC 60598 EN 55015 UL 94 UL 8750 UL 508 A
Ambient Air Temperature for Operation	3...149 °F (-16...65 °C)
Ambient Air Temperature for Storage	14...140 °F (-10...60 °C)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606481203045
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.362 in (6.000 cm)
Package 1 Width	3.150 in (8.000 cm)
Package 1 Length	16.142 in (41.000 cm)
Package weight(Lbs)	29.524 oz (837.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	12.598 in (32.000 cm)
Package 2 Width	16.142 in (41.000 cm)
Package 2 Length	7.087 in (18.000 cm)
Package 2 Weight	18.453 lb(US) (8.370 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	120
Package 3 Height	17.717 in (45.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	288.365 lb(US) (130.800 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	60 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	36
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



