


# Product data sheet

Specifications



## Plain mounting plate H1200xW1000mm Galvanised sheet steel Reversible dimension

NSYMM1210

**Product availability: Stock - Normally stocked in distribution facility**

### Main

|                                    |                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------|
| Range                              | PanelSeT                                                                                   |
| Accessory / separate part category | Mounting accessory                                                                         |
| Product or Component Type          | Mounting plate                                                                             |
| Device Application                 | Multi-purpose                                                                              |
| Enclosure nominal dimensions       | - H: 39.4 in (1000 mm) W: 47.2 in (1200 mm)<br>- H: 47.2 in (1200 mm) W: 39.4 in (1000 mm) |
| Mounting Location                  | Step slide<br>Direct fixing on backstuds                                                   |
| Mounting plate description         | Plain                                                                                      |
| Range compatibility                | PanelSeT S3D<br>PanelSeT CRN<br>PanelSeT PLM                                               |
| Quantity per Set                   | Set of 1                                                                                   |
| Material                           | galvanised steel                                                                           |

### Complementary

|                            |                                                     |
|----------------------------|-----------------------------------------------------|
| Fixing mode                | Screwed on backstuds M8<br>By fixing element        |
| Permanent permissible load | 396.8 lb(US) (180 kg)                               |
| Height                     | 45.3 in (1150 mm)                                   |
| Width                      | 37.4 in (950 mm)                                    |
| thickness                  | 0.07 in (1.8 mm)                                    |
| Product Weight             | 48.246 lb(US) (21.884 kg)                           |
| Variant particularity      | Installation in enclosures with inverted dimensions |

### Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10ES180036  |
| Discount Schedule | 0ES1          |
| GTIN              | 3606480183171 |
| Returnability     | Yes           |
| Country of origin | ES            |

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |                             |
|------------------------------|-----------------------------|
| Nbr. of units in pkg.        | 1                           |
| Package 1 Height             | 1.969 in (5.000 cm)         |
| Package 1 Width              | 37.795 in (96.000 cm)       |
| Package 1 Length             | 45.669 in (116.000 cm)      |
| Package weight(Lbs)          | 50.706 lb(US) (23.000 kg)   |
| Unit Type of Package 2       | PAM                         |
| Number of Units in Package 2 | 12                          |
| Package 2 Height             | 22.835 in (58.000 cm)       |
| Package 2 Width              | 39.370 in (100.000 cm)      |
| Package 2 Length             | 47.244 in (120.000 cm)      |
| Package 2 Weight             | 645.955 lb(US) (293.000 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 236 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 124 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 46 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 0.7 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 66 kg CO2 eq.                                 |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------|
| Packaging made with recycled cardboard | No                                                                          |
| Packaging without single use plastic   | No                                                                          |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |
| PVC free                               | Yes                                                                         |
| Silicon free                           | Yes                                                                         |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                          |
|-------------------------------|------------------------------------------|
| Recyclability potential, in % | 98                                       |
| Circularity Profile           | No need of specific recycling operations |
| Take-back                     | No                                       |