

Product data sheet

Specifications



4 lifting brackets for Spacial SFX enclosure. Max. load 2000kg

NSYPUNX

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Area	PanelSeT
category	Lifting accessory
Product or Component Type	Lifting bracket
Application	Multi-purpose
Mounting Location	Enclosure top
Mounting Support	Directly in the axis of the uprights
Range compatibility	PanelSeT PanelSeT SFX
Device composition	4 bracket
Quantity per Set	Set of 1

Complementary

Material	treated steel
Fixing mode	By screws M12
Permanent permissible load	4409.2 lb(US) (2000 kg) slinging at 60°
Product Weight	10.93 lb(US) (4.96 kg)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480154898
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.953 in (7.500 cm)
Package 1 Width	3.937 in (10.000 cm)
Package 1 Length	9.252 in (23.500 cm)
Package weight(Lbs)	12.311 lb(US) (5.584 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	4

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	11.417 in (29.000 cm)
Package 2 Width	14.764 in (37.500 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	49.242 lb(US) (22.336 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	35 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	22 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	12 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	52da316e-d4e1-4114-85c0-32a03b2934fd
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	98
Circularity Profile	No need of specific recycling operations
Take-back	No