


Product data sheet

Specifications



Door retainer for all versions of PLA -2 positions opening 90° or 120°

NSYRETPLAU

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Door retainer
Application	Multi-purpose
Nominal dimensions of the housing	-
Mounting Location	Door and enclosure
Range compatibility	PanelSeT PLA all versions
Device composition	Fixing elements 1 x retainer

Complementary

Material	galvanised steel
Fixing mode	By fixing element - on enclosure body By fixing element - on door bosses
Operating angle	90 ° 120 °
Opening mechanism	Mechanical system

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480193460
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.945 in (2.400 cm)
Package 1 Width	6.299 in (16.000 cm)
Package 1 Length	9.449 in (24.000 cm)
Package weight(Lbs)	15.732 oz (446.000 g)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product in real life situation

