



Overview

Presentation	NEMA 12 rated assembled enclosure for OT, IT and networking applications. Form factor to easily roll through doorways. Configurable to work as a ventilated enclosure with the addition of Climasys ventilation components. Includes: Front and rear solid doors with handle and insert key, side panels, 19" uprights, bottom plinth, grounding and gland plate at the bottom panel. Ventilation system not included. Can be shipped pre-integrated with UPS, PDU, monitoring components and internal equipment up to 350 lbs.
Lead time	Usually Ships within 4 Weeks

Physical

Height	51.2 in (1300 mm)
Width	23.6 in (600 mm)
Depth	31.5 in (800 mm)
Number of rack unit	24U
Net Weight	220.5 lb(US) (100 kg)
Mounting Mode	Rack-mounted
Mounting preference	No preference
Maximum Mounting Depth	25.7 in (652 mm)
Max CTO ship weight	275.6 lb(US) (125 kg)
Permanent permissible load	249.1 Lb(US) (113 kg) dynamic 881.8 lb(US) (400 kg) static

Ordering and shipping details

Category	US10ES180035
Discount Schedule	0ES1
GTIN	3606481008756
Returnability	Yes
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	58.3 in (148.0 cm)
Package 1 Width	29.1 in (74.0 cm)
Package 1 Length	45.7 in (116.0 cm)
Package 1 Weight	332.90 lb(US) (151.00 kg)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--