

Product data sheet

Specifications



Interlocking system for secondary doors, PanelSeT SFN, PanelSeT SF, for electrical enclosure W600mm , steel

NSYSLCKS6

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Interlocking for secondary door
Application	Automobile application
Nominal dimensions of the housing	-
Mounting Location	On top structure of secondary enclosures
Mounting Support	Interlocking for main door Activation for secondary doors
Device composition	Fixing elements 1 x mechanism
Quantity per Set	Set of 1

Complementary

Material	steel
Surface Finish	Zinc coated
Fixing mode	By screws - on structure
Width	Nominal: 23.6 in (600 mm)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480067822
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.756 in (7.000 cm)
Package 1 Width	3.740 in (9.500 cm)
Package 1 Length	24.016 in (61.000 cm)
Package weight(Lbs)	32.804 oz (930.000 g)
Unit Type of Package 2	PAL

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 2	20
Package 2 Height	7.480 in (19.000 cm)
Package 2 Width	14.764 in (37.500 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	41.006 lb(US) (18.600 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	7 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	52da316e-d4e1-4114-85c0-32a03b2934fd
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	98
Circularity Profile	No need of specific recycling operations
Take-back	No