

Product data sheet

Specifications



set of 4 Spacial SM M12 lifting eyebolt - galvanized cast steel

NSYSMEB

Product availability: Stock - Normally stocked in distribution facility

Main

Area	PanelSeT
category	Lifting accessory
Product or Component Type	Lifting bracket Lifting eye
Application	Multi-purpose
Mounting Location	Enclosure top
Range compatibility	PanelSeT PanelSeT SF PanelSeT PanelSeT SM
Device composition	4 eyebolt 4 fixing nuts
Quantity per Set	Set of 1

Complementary

Material	cast steel
Surface Finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	749.6 lb(US) (340 kg) for 1 eyebolt vertical direction
Height	2.4 in (61.5 mm)
Width	2.1 in (54 mm)
Depth	1.02 in (26 mm)
Diameter	1.1 in (29 mm)
ISO thread	M12

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480146596
Returnability	Yes
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.362 in (6.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	5.709 in (14.500 cm)
Package weight(Lbs)	2.332 lb(US) (1.058 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	240
Package 2 Height	17.717 in (45.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	610.681 lb(US) (277.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicon free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	98
Circularity Profile	No need of specific recycling operations
Take-back	No