

Product data sheet

Specifications



PC box IP66 IK08 RAL7035
Int.H175W150D100
Ext.H193W164D105 opaque PC
cover H40

NSYTBP191610H

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Product name	PanelSeT TBP
Device Application	Multi-purpose
Category	Industrial box
Height	7.6 in (192 mm)
Width	6.5 in (164 mm)
Depth	4.1 in (105 mm)
Internal height	6.9 in (175 mm)
Internal width	5.9 in (150 mm)
Internal depth	3.9 in (100 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	polycarbonate
color	Gray RAL 7035)
Standards	UL 508 A IEC 62208
Product Certifications	TÜV UL
Electrical Insulation Class	Class II
Mounting location	Outdoor (with canopy or shelter and anticondensation valve)
Product Weight	1.37 lb(US) (0.62 kg)

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
-------------------------	------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5...140 °F (-15...60 °C)
Operating temperature	-13...176 °F (-25...80 °C)

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480165672
Returnability	Yes
Country of origin	HU

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.724 in (12.000 cm)
Package 1 Width	6.693 in (17.000 cm)
Package 1 Length	8.071 in (20.500 cm)
Package weight(Lbs)	21.058 oz (597.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	17
Package 2 Height	15.748 in (40.000 cm)
Package 2 Width	16.142 in (41.000 cm)
Package 2 Length	24.016 in (61.000 cm)
Package 2 Weight	22.375 lb(US) (10.149 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	204
Package 3 Height	52.953 in (134.500 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	293.215 lb(US) (133.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.8 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No

Technical Illustration

Dimensions




Image of product / Alternate images

Alternative



Image of product in real life situation

