


Product data sheet

Specifications



Terminal Blocks, Linergy, fused block, 12A, 600V, screw, for 5X20/25/30mm fuses, with 110/250V LED, 2 points, black

NSYTRV42SF5LA

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Linergy
Product name	Linergy TR
Product or Component Type	Terminal block
Device short name	TRV
Terminal block type	Fused disconnect
Terminal block level	1
Mounting Mode	Clip-on
Nominal cross section	0.006 in² (4 mm²)
Length	2.9 in (72.5 mm)
color	Black
Quantity per Set	Set of 50

Complementary

Fuse size	5 x 20 mm
Width	0.3 in (8.2 mm)
Height	2.2 in (56.5 mm)
Connections - terminals	1 x screw terminal upstream 1 x screw terminal downstream
number of connections	2
Connection position	Sideways
Number of measurement input	0
Cable cross section	0.0003...0.006 in² (0.2...4 mm²), flexible without cable end 0.0003...0.006 in² (0.2...4 mm²), solid
Tightening torque	4.4...7.08 lbf.in (0.5...0.8 N.m)
Wire stripping length	0.3 in (8 mm)
Tool type	Connection screwdriver Disconnection screwdriver
[Ue] rated operational voltage	500 V EN/IEC 60947-7-1 600 V UL 600 V CSA
Line Rated Current	6.3 A EN/IEC 60947-7-1 12 A UL 6.3 A CSA
Material	Polyamide 6/6: insulating case

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Dielectric loss	0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m IEC 60093 10000 MΩ.m VDE 0303-T30
Surface resistance	1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) IEC 60093 500 CTI (> 400 kB) VDE 0303-T30
Flame retardance	V0 0.03 in (0.8 mm) UL 94
Product Weight	0.7 oz (20 g)
Provided equipment	110...250 V light indicator
Range compatibility	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product Compatibility	Spacial enclosures

Environment

Product Certifications	UL CSA
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40...266 °F (-40...130 °C) IEC 60216-1 -40...266 °F (-40...130 °C) VDE 0304-T21

Ordering and shipping details

Category	US10CP521715
Discount Schedule	0CP5
GTIN	3606480532351
Returnability	Yes
Country of origin	TR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.480 in (6.300 cm)
Package 1 Width	4.331 in (11.000 cm)
Package 1 Length	2.441 in (6.200 cm)
Package weight(Lbs)	0.670 oz (19.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	2.480 in (6.300 cm)
Package 2 Width	4.331 in (11.000 cm)
Package 2 Length	12.205 in (31.000 cm)

Package 2 Weight	35.203 oz (998.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	400
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	18.497 lb(US) (8.390 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	6 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	8e5413ff-f1a1-4909-ad03-977097e33bd2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	46
Circularity Profile	No need of specific recycling operations
Take-back	No

