

Product data sheet

Specifications



Vertical uprights height 1500mm.
zinc-coated steel. Supply: 2
standard uprights.

NSYTVR15

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range	PanelSeT
Accessory / separate part category	Mounting accessory
Product or Component Type	Technical upright
device application	Multi-purpose
enclosure nominal dimensions	- H: 59.06 in (1500 mm)
Mounting Support	Step slide Direct fixing on the rear inserts
Range compatibility	PanelSeT PLA
Device composition	2 upright
Material	steel

Complementary

Surface Finish	Zinc coated
Fixing mode	Bosses inserts M8 - rear of enclosure
Adjustment	Adjustable in depth every 25 mm with caged nuts Adjustable in height every 2.5 mm with quarter-turn nuts
Height	Nominal: 59.06 in (1500 mm) Real: 54.1 in (1375 mm)
Width	1.8 in (45 mm)
Depth	1.3 in (34 mm)
thickness	0.08 in (2 mm)
Cut-out dimensions	11 x 13 mm

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480185076
Returnability	No
Country of origin	IT

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	1.575 in (4.000 cm)
Package 1 Width	2.362 in (6.000 cm)
Package 1 Length	54.331 in (138.000 cm)
Package weight(Lbs)	9.114 lb(US) (4.134 kg)
Unit Type of Package 2	P2M
Number of Units in Package 2	120
Package 2 Height	19.685 in (50.000 cm)
Package 2 Width	47.244 in (120.000 cm)
Package 2 Length	78.740 in (200.000 cm)
Package 2 Weight	1102.312 lb(US) (500.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	29 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	18 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.8 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	10 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	98
Circularity Profile	No need of specific recycling operations
Take-back	No