

Product data sheet

Specifications



19" swing chass 20U W800 Spacial

NSYVDM20U8P

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Accessory / separate part category	Mounting accessory
Product or Component Type	19" rack
Application	Electronic application Multi-purpose
For enclosure nominal dimensions	- H: 39.4 in (1000 mm) W: 31.5 in (800 mm) D: 9.8 in (250 mm) - H: 39.4 in (1000 mm) W: 31.5 in (800 mm) D: 11.8 in (300 mm) - H: 39.4 in (1000 mm) W: 31.5 in (800 mm) D: 15.7 in (400 mm)
Rack type	Swing
Mounting Location	Front of enclosure
Range compatibility	PanelSeT PanelSeT S3D PanelSeT PanelSeT S3X PanelSeT PanelSeT VDM PanelSeT PanelSeT CRN PanelSeT PanelSeT CRNG
Device composition	fixing elements 1 19" swing chassis 2 lock
Number of units 19"	20

Complementary

Material	Chassis steel
Enclosure/cubicle description	Wall-mounted enclosure
Surface Finish	Epoxy-polyester powder
Lock type	Lock with 3 mm double bar insert
Fixing Mode	By fixing element
color	Gray RAL 7035)
Permanent permissible load	6.6 lb(US) (3 kg) per unit
Opening of the 19" racks	Reversible 120 °
Height	Nominal: 39.4 in (1000 mm)
Width	Nominal: 31.5 in (800 mm)
Depth	5.1 in (130 mm)
Product Weight	25.6 lb(US) (11.6 kg)

Ordering and shipping details

Category	US10ES180036
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	0ES1
GTIN	3606480174742
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.118 in (13.000 cm)
Package 1 Width	32.283 in (82.000 cm)
Package 1 Length	37.402 in (95.000 cm)
Package weight(Lbs)	24.471 lb(US) (11.100 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	8
Package 2 Height	40.945 in (104.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	222.447 lb(US) (100.900 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	105 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	22 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	26 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	E893f0a0-d2cc-4011-9425-3873dde70142
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No