

Product data sheet

Specifications



Discrete Output Module + Base,
Edge I/O NTS, 4 Out, 24V DC,
500mA, Source, Diagnostics,
Protected, 1/2/3 Wires, Modicon
Edge I/O NTS

NTSDDO0402K

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon Edge I/O NTS
Product or Component Type	Discrete output module kit
Kit composition	NTSDDO0402 module NTSXBA0100H base
Mandatory accessory	NTSXTB12_0_H terminal block
Product Compatibility	NTSN.....
Range Compatibility	Logic/motion controller - Modicon M262 Modicon M580 Third party
Device Application	Industrial Application
Discrete output number	4
Group of output channels	1 group
Discrete output logic	Positive logic (source)
Discrete output voltage	24 V DC
Operating Mode	Synchronous/Isochronous

Complementary

Discrete output number	4 transistor
Output wiring mode	1, 2 or 3 wires
Discrete output current	500 mA per channel 2 A per module
Discrete output frequency	1 kHz for resistive load 0.5/LI² Hz for inductive load
Response time on output	90 µs maximum (turn on) 110 µs maximum (turn off)
Maximum leakage current	0.002 mA per channel
Maximum voltage drop	<0.1 V per channel DC
Maximum tungsten load	<12 W
Output protection type	Transient voltage suppression per channel Short circuit protection per channel Overload/thermal protection per channel Reverse polarity protection per module

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output diagnostic	Power supply error per channel Broken wire error per channel Over current error per channel Read back error per channel
Power supply type	Bus power from power supply bus (24 Vdc) Field power from power supply field (24 Vdc)
Rated operational voltage limits	20.4...28.8 V DC
Typical current consumption	30 mA 24 V DC on the Bus current 8.4 mA 24 V DC on the internal field current minimum 2010.1 mA 24 V DC on the internal field current maximum
Electrical Connection	Screw/spring terminal block
Power dissipation in W	1.27 W maximum at 24 V DC
Isolation between channels and bus	1500 V AC
Isolation between channels and ground	1500 V AC
Hot swapping fallback	Yes
Local signalling	1 LED (green) for module operating (RUN) 1 LED per channel (green) for channel diagnostic 1 LED (red) for module error (ERR)
Housing Colour	Grey
Mounting support	Top hat type TH35-7.5 rail IEC 60715 Top hat type TH35-15 rail IEC 60715
Height	3.9 in (100 mm)
Width	0.6 in (15 mm)
Depth	3.1 in (80 mm)
Product Weight	0.161 lb(US) (0.073 kg)

Environment

IP Degree of Protection	IP20
Marking	CE UKCA CULus RCM
Product certifications	CE UKCA CULus RCM Merchant Navy - EU RO MR (pending) EAC (pending) ATEX Zone 2 (pending) IECEx zone 2 (pending) CCC Ex zone 2 (pending)
Standards	EN/IEC 61131-2 EN 61010-2-201 UL 61010-2-201 IACS E10 EN/IEC 61000-6-5, interface type 1 and type 2 EN/IEC 61850-3, location G EN/IEC 60079-0 EN 50155 EN 50121-4 EN 50121-5
Directives	2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive 2014/35/EU
Ambient air temperature for operation	-4...140 °F (-20...60 °C)

Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	5...95 % without condensation
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000...5000 m with derating
Pollution degree	2
Environmental characteristic	Gas resistant C3 and G2
Vibration resistance	1 g without accessory 2 g with accessory
Shock resistance	15 g 11 ms with and without accessory)

Ordering and shipping details

Category	US1PC3318214
Discount Schedule	PC33
GTIN	3606487024545
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.0 in (2.5 cm)
Package 1 Width	3.3 in (8.3 cm)
Package 1 Length	4.6 in (11.6 cm)
Package weight(Lbs)	2.70 oz (76.65 g)
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Height	5.9 in (15 cm)
Package 2 Width	5.9 in (15 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	3.1429 lb(US) (1.4256 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	31 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	22 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	36da5072-249a-4bb2-ac87-86507dce031e
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Recyclability potential, in %	0
Circularity Profile	End of Life Information
Take-back	No


Dimensions Drawings

Dimensions



Mounting and Clearance

Minimum clearances




a : 50 mm (1.97 in) **b** : Without EMC kit: 25 mm (0.98 in), with EMC 55 kit: 55 mm (2.16 in) **c** : 80 mm (3.15 in) **d** : 25 mm (0.98 in)

Connections and Schema


Wiring

2-wire or 3-wire connection



Technical Illustration

Dimensions



Technical Illustration

Wiring diagram

2-wire or 3-wire connection




Image of product / Alternate images

Alternative








Image of product in real life situation

