

Product data sheet

Specifications



EcoStruxure Panel Server Wired by Design - universal concentrator modbus gateway POE

PAS600PWD

Product availability: Stock - Normally stocked in distribution facility

Main

Range	EcoStruxure
Product name	Panel Server Universal Wired by Design
Product or Component Type	Gateway
Device short name	PAS600PWD
Device Application	Gateway
[Us] rated supply voltage	PoE
Communication gateway	Ethernet/serial

Complementary

Communication port protocol	Modbus TCP DHCP HTTPS NTP/SNTP IPv4 IPv6 TCP/IP
Communication port support	2 RJ45 ETHERNET Screw terminal block RS485
Number of server device(s)	32 Modbus RTU product(s) 128 Modbus TCP/IP product(s)
Number of devices	64 Modbus TCP/IP
Number of inputs	0
Connections - terminals	Power supply screw terminal block top) 0.002...0.004 in ² (1.5...2.5 mm ²) Communication screw terminal block bottom) 0.0002...0.002 in ² (0.14...1.5 mm ²)
Tightening torque	Power supply: 5.3 lbf.in (0.6 N.m) Communication: 2.21 lbf.in (0.25 N.m)
Wire stripping length	Power supply: 0.3 in (7 mm) Communication: 0.3 in (7 mm)
Mounting Mode	Clip-on
Mounting Support	DIN rail
Product Certifications	CE cULus CB RCM UKCA FCC IC DNV Marine IACS E10

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	IEC 61010 IEC 61010-1 IEC 61010-2-201 UL 61010 UL 61010-1 UL 61010-2-201 EN 61010-1 EN 61010-2-201 CAN/CSA C22.2 No. 61010-1-12 CAN/CSA C22.2 No. 61010-2-201 IEC 62974-1 IEC 61326-1 EN 61326-1 EN 55032 CISPR 11 FCC CFR 47 part 15 class A IEC 60945 EN 62974-1 DNVGL-GC-0339 IEC 62947-1
Depth	2.8 in (70.2 mm)
Height	3.7 in (93 mm)
Width	2.8 in (72 mm)
Product Weight	6.4 oz (182 g)
Data recording	Real time data monitoring
Data buffer for data publication (cloud, SFTP, HTTPS) depending on network	1 month(s)
Function Available	Embedded web page for configuration and upgrade Diagnosis capabilities Diagnostic report Diagnostics on communication Energy management With integrated web server Firmware update Backup/restore configuration Configurable event
Topology	Separated Ethernet network Switched Ethernet network
Web services	HTTPS server SFTP publication (CSV / JSON) HTTPS publication (CSV / JSON)
Communication Service	Device Profile for Web Services (DPWS) Modbus TCP client Modbus TCP server SNTP client DHCP client DHCP server RSTP
Commissioning interface	EcoStruxure Power Commission desktop EcoStruxure Power Commission web (for third party device integration) Web page
Realtime clock	With RTC-battery set With user calibration
Time synchronisation protocol	NTP SNTP
Range compatibility	EcoStruxure Facility Expert EcoStruxure Building Operation EcoStruxure Power Operation EcoStruxure Power Monitoring Expert EcoStruxure Asset Advisor EcoStruxure Energy Hub EcoStruxure Resource Advisor Third party SCADA
Communication iinterface	Modbus product

Environment

Relative humidity	0...93 %
IP degree of protection	IP40 front face) IP20 casing)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Pollution degree	2
Operating altitude	< 2300 m

Ordering and shipping details

Category	US10PL109785
Discount Schedule	0PL1
GTIN	3606487131434
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.346 in (8.500 cm)
Package 1 Width	3.465 in (8.800 cm)
Package 1 Length	4.331 in (11.000 cm)
Package weight(Lbs)	8.536 oz (242.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	15.767 lb(US) (7.152 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	131 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	18 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	111 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	8fd200e0-fc2c-4c52-ba68-62f2aced16fe
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	1
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No

WEEE Label




The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

mm
[in]



Technical illustration

Product Installation

