

Product data sheet

Specifications



J-Frame ATS, ASCO Series 300,
open transition, 3 pole, 600A,
480V, Type 3R secure, with 11BE,
44G, SEB, Cat#
J03AUSA30600NGXM, 11BE, 44G
[TAA]

PPATS_1454629

Main

Switch Series	ASCO 300 Series
Product or Component Type	Transfer switch
Rated Current	600 A
Number of Phases	Three phase
Number of Poles	3P
Rated Voltage	480 V

Complementary

Neutral Configurations	Solid neutral
Transition Mode	Open
Operation Mode	Automatic
Hot to Hot Transfer Time	< 80 ms
Controller	Group G
Communication Capability	Modbus TCP RS485
Service Entrance Rated	Service entrance rated
Center Off Position	No
Enclosure Options	UL Type 3R Secure
Switch Frame	J-Frame

Ordering and shipping details

GTIN	3606487236658
------	---------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	95.4 in (242.4 cm)
Package 1 Width	32.6 in (82.9 cm)
Package 1 Length	32.6 in (82.9 cm)
Package weight(Lbs)	1215.0 lb(US) (551.1 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Compliance

Compliance	TAA Compliant
------------	---------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No