

Product data sheet

Specifications



Charging station cable, Schneider Charge Pro AC, 11.5kW, 48A, 208/240VAC, SAE J3400

PROAC48J3400CBLE

⚠ Launching in: 1 June 2026

⚠ Coming soon

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	Schneider Charge Pro
Product or Component Type	Charging cable

Complementary

Connector Type	SAE J3400
Socket number	1
Standards	UL 50
Ambient Air Temperature for Storage	-40...140 °F (-40...60 °C)
Relative humidity	5...95 %
Maximum supply current	48 A
Ambient air temperature for operation	-22...122 °F (-30...50 °C)
IP degree of protection	IP67
Nominal output power	11.5 kW 48 A 208/240 V AC
Operating altitude	0...6561.68 ft (0...2000 m)
[Ue] rated operational voltage	208/240 V AC 60 Hz
Product Weight	7.5 lb(US) (3.4 kg)
Quantity per Set	1
Targeted country	USA Canada

Ordering and shipping details

Category	US1DE1021002
Discount Schedule	DE10
GTIN	3606487186694
Returnability	No
Country of origin	TH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.0 in (15.2 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	22.008 in (55.9 cm)
Package 1 Length	22.008 in (55.9 cm)
Package weight(Lbs)	15.0 lb(US) (6.8 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Removable battery	No
Take-back	No