

Product data sheet

Specifications



Charging station, Schneider Charge Pro AC, 11.5kW, 48A, 208/240VAC, wall mounted, SAE J3400

PROAC48USJ3400EVC

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Schneider Charge Pro
Product name	Schneider Charge Pro
Product or Component Type	Charging station

Complementary

Mounting Mode	Wall-mounted Pedestal mount
Offer type	Advanced
Connector Type	SAE J3400
Socket number	1
Number of inputs	1
Protection Type	Surge
Standards	UL 2594 UL 2231-1 UL 2231-2 UL 1998
Product Certifications	UL/cUL listed ENERGY STAR (USA) FCC part 15 class B RoHS REACH
Ambient Air Temperature for Storage	-40...140 °F (-40...60 °C)
Relative humidity	5...95 %
Maximum supply current	48 A
Communication Network Type	Mobile network Wi-Fi Ethernet
Communication port protocol	OCPP
Ambient air temperature for operation	-22...122 °F (-30...50 °C)
IK degree of protection	IK10
IP degree of protection	NEMA 4
Nominal output power	11.5 kW 48 A 208/240 V AC
Operating altitude	0...6561.68 ft (0...2000 m)
[Ue] rated operational voltage	208/240 V AC 60 Hz
Height	16.0 in (406 mm)
Width	7.2 in (184 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	5.4 in (138 mm)
Product Weight	18.3 lb(US) (8.3 kg)
Quantity per Set	1
Targeted country	USA Canada

Ordering and shipping details

Category	US1DE1021002
Discount Schedule	DE10
GTIN	3606487186663
Returnability	Yes
Country of origin	TH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	12.008 in (30.5 cm)
Package 1 Width	22.008 in (55.9 cm)
Package 1 Length	28.0 in (71.1 cm)
Package weight(Lbs)	30.0 lb(US) (13.6 kg)

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	759 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	233 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	26 kg CO2 eq.
Carbon footprint of the installation phase [A5]	3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	476 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	21 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No