

Product data sheet

Specifications



Flexset Switchboard, PowerPacT R, Busbar, Three-phase, Micrologic 6.0 A LSIG, 1200A, 600VAC, 65kA, 80%

RKF36120U44AFLEX

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Circuit breaker
Range	FlexSet Switchboards
Current Sensor Rating Range	1200 A
Rated Current	1200 A
Breaking Capacity	65 kA 240 V AC 65 kA 480 V AC 65 kA 600 V AC
Trip Unit Technology	Electronic, ammeter, MicroLogic 6.0 A, LSIG

Complementary

Certifications	CSA IEC UL Listed
Rated operational Voltage	600 V AC
Mounting Location	Busbar
Mounting Mode	Unit mount
Poles Description	3-pole
Circuit Breaker Rating Code	K
Continuous Current Rating	80 %
Electrical Connection	Busbar connection, line Busbar connection, load
Tightening Torque	601.8 lbf.in (68 N.m) 0.08...0.6 in² (50...400 mm²) (AWG 1/0...750 kcmil) 601.8 lbf.in (68 N.m) 0.08...0.2 in² (50...150 mm²) (AWG 1/0...300 kcmil)
Height	16.24 in (412.50 mm)
Width	16.53 in (419.86 mm)
Depth	14.49 in (368.05 mm)
Provided Equipment	1 x 1 x wiring harness connector

Ordering and shipping details

Category	US1FLEX00077
Discount Schedule	FLEX
GTIN	3606482215146
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	US
-------------------	----

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.910 in (15.011 cm)
Package 1 Width	9.850 in (25.019 cm)
Package 1 Length	11.820 in (30.023 cm)
Package weight(Lbs)	48.500 lb(US) (21.999 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 595 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	101 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 455 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	28 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	E0af0645-a161-4464-bcbd-19783d1f9e01
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	88
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No

